

**FOTOMILE VISTA 4MP
Vandal-Resistant Network
Dome Camera**



KEY FEATURES

**FMVistaVS428-VDR-Vandal
Resistant Network Fixed Dome Camera**

- Smart IR, Up to 30 m (98 ft) IR distance
- Ultra 265, H.265, H.264, MJPEG
- ONVIF Conformance
- Wide temperature range: -30deg C to 60deg C (-22deg F TO 140deg F)
- Wide voltage range of +/-25%
- IK10 Vandal resistant
- IP67

FMVistaVS428-VDR



Fotomile
VISTA

FOTOMILE VISTA 4MP Vandal-Resistant Network Dome Camera

Technical Specs - FMVistaVS428-VDR

Lens & Sensor	2.8mm@f2.0, 1/3", progressive scan, 4.0megapixel, CMOS			
View Angle	Angle of view(H)	Angle of view(V)	Angle of view(O)	Adjustment Angle
	104H	54V	135	Pan: 360deg C
	78	39	97	Tilt : 75deg C
Day/Night	IR-cut filter with auto switch(ICR)			
Digital noise reduction	2D/3D DNR			
IR Range	up to 30(98 ft) IR range			
WDR	DWDR			
Video Codes	Ultra 265, H.265, H.264, MJPEG			
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, Upnp, HTTPS, SMTP, SSL			
Network	1 RJ45100M Base -TX Ethernet			
Power	DC12V+-25%, PoE(IEEE802.3af)			
	Power consumption: Max.4w			
Dimensions(φXH)	φ109X81mm (φ5.8"X4.4")			
Weight	0.35kg (0.77lb)			
Working Environment	-30°C ~ +60°C, Humidity: 10% ~90% RH			
Protection Class	IK10, IP67			