



fotomile
VISTA

FOTOMILE VISTA 2MP IP Bullet Camera



FMVista VSFIR230-O

KEY FEATURES

FMVista VSFIR230-O Network Bullet Camera

- Smart IR ,Up to 30 m (98 ft) IR distance
- Ultra 265, H.265, H.264, MJPEG
- ONVIF Conformance
- Wide temperature range: -30°C to 60°C (-22°F to 140° F)
- Wide voltage range of +-25%
- IP66

contact@fotomile.co.uk

www.fotomile.co.uk



Fotomile
VISTA

FOTOMILE VISTA 2MP IP Bullet Camera

Technical Specs - FMVista VSFIR230-O

Lens & Sensor	4.0mm@F1.6,1/2 , Progressive scan, 2.0megapixel, CMOS			
View Angle	Angle of view(H)	Angle of view(V)	Angle of view(O)	Adjustment Angle
	80.8	44.1	99.4	Pan: 360°C
	54.9	30.2	67.5	Tilt : 90°c/Rotate:360°
Day/Night	IR-cut filter with auto switch (ICR)			
Digital noise reduction	2D/3D DNR			
IR Range	up to 30mm(98 ft) IR range			
WDR	DWDR			
Video Codes	Ultra 265, H.265, H.264, MJPEG			
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, Upnp, HTTPS, SMTP, 802.1X			
Network	1 RJ4510/100M Base -TX Ethernet			
Power	12VDC+-25%, PoE(IEEE802.3af)			
	Power consumption: Max.6.4w			
Dimensions(LXWXH)	157.3X63X62			
Weight	0.45kg (0.99lb)			
Working Environment	-35°C~+60°C, Humadity: 10%~95%RH			
Protection Class	IP67			