

FOTOMILE VISTA 2MP Vandal-Resistant Network Dome Camera



KEY FEATURES

FMVistaVS228-VDR-Vandal Resistant Network Fixed Dome Camera

- Smart IR, Up to 30 m (98 ft) IR distance
- Ultra 265, H.265, H.264, MJPEG
- ONVIF Conformance
- Wide temperature range: -30deg C to 60deg C
(-22deg F TO 140deg F)
- Wide voltage range of +/-25%
- IK10 Vandal resistant
- IP67

FMVistaVS228-VDR



FOTOMILE VISTA 2MP Vandal-Resistant Network Dome Camera

Technical Specs - FMVistaVS228-VDR

Lens & Sensor	2.8mm@f1.8, 1/2.8", progressive scan, 2.0megapixel, CMOS
View Angle (H)	112°
Day/Night	IR-cut filter with auto switch(ICR)
Digital noise reduction	2D/3D DNR
IR Range	up to 30(98 ft) IR range
WDR	DWDR
Video Codes	Ultra 265, H.265, H.264, MJPEG
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, Upnp, HTTPS, SMTP, SSL
Network	1 RJ45100M Base -TX Ethernet
Power	DC12V+-25%,PoE(IEEE802.3af) Power consumption :Max.4w
Dimensions (φXH)	φ109X81mm(φ5.8"X4.4")
Weight	0.35kg(0.77lb)
Working Environment	-30°C ~ +60°C, Humidity: 10% ~90% RH
Protection Class	IK10, IP67