

PRESENTING THE TERZOCCHIO SERIES OF NVRS....



WITH TERZOCCHIO, THE THIRD EYE, GET YOURSELF

- A high performance network video recorder with the best quality Components.
- High durability, champion performance and minimum downtime are our assurance.
- Its tough exterior protects the components even in adverse outdoor conditions.

Four high RPM fans keep the components ventilated and temperatures low. What you get is 24/7 operational capacity and 30% more durability of the components.

UNLIKE OTHER PRODUCTS IN ITS SEGMENT, THE TERZOCCHIO SERIES:

- Dedicates a RR (recording rate) of 30 FPS (frames per second) for each of its channels.
- Doesn't have a fixed TRR (total recording rate). The TRR is divided amongst the all the channels. So the TRR increases with the number of channels ensuring Live Playback.
- Ensure minimum downtime and top-notch performance with superior quality components, processor and graphic cards.
- All service, troubleshooting and up-gradation problems are solved with Fotomile that ensures that the CPI (channel partner and implementer) are completely equipped and trained.

THERE'S MORE...

- Finest compression technology for video transmissions over minimum bandwidth.
- Wi-fi connectivity.
- Scaleable built-in storage up to 2-terra-bytes and backup-facility on DVD and USB.

Get Maximum value for your money only with

TERZOCCHIO

Keep third eye on your business ...

TERZOCCHIO Standard system specifications (all models)

Model	TERZOCCHIO 16	TERZOCCHIO 32
Video / Audio Input		
IP Video / Audio	16-ch	32-ch
Two-way Audio Input	1-ch, RCA	
Network		
Incoming Bandwidth	160Mbps	200 MBps
Outgoing Bandwidth	96Mbps	
Remot users	128	
Video / Audio Output		
HDMI/VGA Output	HDMI/VGA 1920 x 1080p / 60Hz, 1920 x 1080p / 50Hz, 1600x1200 / 60Hz, 1280x1074 / 60Hz, 1280x720 / 50Hz, 1280x768 / 60Hz	
Recording Resolution	4MP/3MP/1080p/720p/D1/2CIF/CIF	
Audio Output	1-ch, RCA	
Synchronous Playback	16-ch	
Decoding		
Compression	H.264	
Live view / Playback	4MP/3MP/1080p/720p/D1/2CIF/CIF	
Capability	4x4MP@20, 6x1080@25, 16x720@25, 32x01	
Hard Disk		
SATA	8 SATA interfaces	
Capacity	up to 6TB for each disk	
External Interface		
Network Interface	2 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface	
Serial Interface	1 x RS232, 1 x RS485	
USB Interface	Front Panel: 1 x USB2:0 Rear Panel: 1 x USB2:0, 1 x USB3:0	
Alarm in	B-ch	
Alarm Out	2-ch	
General		
Power Supply	100 - 240 VAC	
Consumption (without HDD)	15W	
Working Temperature	-10°C + 55°C (+14oF +131°F)	
Working Humidity	10% - 90%	
Dimensions	86 x 442 x 421mm (3.4" x 17.4" x 16.6")	
Weight / without HDD	5.16Kg (11.38lb)	

