

4K UltraHD Vandal-resistant Fisheye Dome Camera



FMFEY932-VF-VRD:

- Ultra wide angle lens, 360° panoramic image
- Embedded infrared light, 360° fill-in-light, up to 10m (33ft) IR distance
- 2D/3D DNR (Digital Noise Reduction)
- Max. 4000 * 3000 resolution
- Ultra265, H.265, H.264, MJPEG
- Built-in microphone & speaker, two-way talk supported
- Distortion correction supported
- ONVIF Conformance
- Wide temperature range: -30°C to 60°C (-22°F to 140°F)
- IK10 & IP66

Technical Specs FMFEY932-VF-VRD

Sensor and Lens	1/1.7", progressive scan, 12.0 megapixel, CMOS, 1.8mm@f2.4
View Angle (H)	360°
Day/Night	IR-cut filter for day and night function
Digital noise reduction	2D/3D DNR
IR Range	up to 10m(33ft)
WDR	DWDR
Compression	Ultra 265, H.265, H.264, MJPEG
Fisheye Frame rate	Main Stream: 15fps(4000x3000,3000x3000), 25fps(2560x2560)
	Sub Stream: 15fps(2000x1500,2000x2000), 25fps(2000x2000)
	Third Stream : 15fpsw(720x576,320x288)
Panorama	25fps(3000x2000)
	15fps(4000x3000, 3000x2000, 3000x1500)
Frame rate PTZ	15fps(1920x1080)
ROI	Up to 8areas
OSD	Up to 8 OSDs
Privacy Mask	Up to 8 Areas
Motion of Detection	Up to 4 areas
Two - way audio	Supported
Edge Storage	Micro SD, Up to 256GB
Network Storage	ANR
Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPOe, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP
Compatible integration	ONVIF(Profiles, Profile G, Profile T)API
Mount Type	Support table, wall, ceiling
Built in Mic	Supported
Built -in Speaker	Supported
Serial	1 Channel RJ485 Interface
Network	1 RJ45 10M/100 Base -TX Auto-adaptive ethernet
Video Output	1 BNC, Impedance 75Ω, Amplitude 1V[p-p]
Dimensions(φxh)	φ149mmx51.5mm(φ5.87"x2.0")
Weight	0.5kg(1.1lb)
Work Envirment	-35°C~60°C(-31°F~140°F)Humadity:10%10%~90%RH
Ingress Protection	IP66
Vandal Resistant	IK10